

# PRODUCT INFORMATION



Automotive Chemicals – Coolant Antifreeze

Version: 2011/28#1

## Valvoline™ ZEREX™ G48® RTU

*Hybrid coolant for passenger car, heavy duty truck, bus and off-road applications.*

Valvoline ZEREX G48® RTU is an official GLYSANTIN® based premium coolant suitable for passenger cars, light trucks and heavy-duty applications. The formulation is ethylene glycol-based and it is designed for all types of engines. It is a low-silicate, low pH, phosphate free technology based coolant that protects all cooling system metals, including aluminum, from corrosion. Valvoline ZEREX G48® RTU protects engine components from winter freezing and summer boiling. Valvoline ZEREX G48® RTU is ready to use and must not be mixed with (demineralized) water.

GLYSANTIN® G48® by BASF is approved by:
BMW / MINI : BMW GS 94000
Bez. Reg. Amsberg, Dept. of Mining and Energy 84.12.22.63-2001-2
MB-Approval 325.0
Deutz DQC CA-14
German Army TL 6850-0038/1
Jenbacher TA-Nr. 1000-0201
Liebherr Minimum LH-00-COL3A
MAN 324-NF
MAN Diesel & Turbo Liste 3.3.7
Maybach / Smart (MB-Approval 325.0)
MTU MTL 5048
Opel / Vauxhall (until 2000) B 040 0240
Porsche (until 1995)
Rolls-Royce (from 1998) : BMW GS 94000
Saab 690 1599
Tesla (from 2013)
Van Hool
TL 774-C: VW / Audi / Seat / Skoda
Volvo Truck (until 2005)
Zastava

Performance levels
AFNOR NF R 15-601
AS 2108-2004
ASTM D 3306
ASTM D 4985
BS 6580:2010
China GB 29743-2013
CUNA NC 956-16
JIS K 2234:2006
ONORM V 5123
SAE J1034
SANS 1251:2005

### Features and Benefits

#### Premium formula for superior protection

Valvoline ZEREX G48® is an OEM approved premium grade hybrid technology based coolant that provides outstanding protection to vital engine parts such as coolant channels in engine block, cylinder heads (liner pitting), radiator and water pump against corrosion, overheating and frost. It contains high quality defoamer and will not harm gaskets, hoses, plastics or original vehicle paint.

#### Long Life Protection

Superior long-life protection:

- up to 5 years / 250.000 km for passenger cars
- up to 3 years / 500.000 km for Heavy Duty applications



Glysantin® and G48® are brands of BASF – We create chemistry

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineurope.com](http://www.valvolineurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline ZEREX G48® RTU	
Ready to use	
Appearance	Liquid
Colour	Blue-green
Boiling point °C, ASTM D 1120	165 min.*
Flash point °C, DIN ISO 2592	120 min.
Density g/cm <sup>3</sup> @ 20 °C, DIN 51 757-4	1,072 – 1,074
pH value, ASTM D 1287	7,9 – 8,3
Viscosity mm <sup>2</sup> /s @ 20 °C, DIN 51 562	24 – 28
Ash content % ASTM D 1119	Max. 1,5
Storage stability	Up to 3 years

\* Boiling Point shown using conventional 15 psi Radiator cap.

This information only applies to products manufactured in the following location(s):  
Europe

™ Trademark of Valvoline, registered in various countries © 2017  
© = Registered trade mark of BASF SE

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.



## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

## Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

## Freezing Temperature:

Ready to use product: -38°C



Glystantin® and G48® are brands of BASF – We create chemistry